



**Europäisches
Patentamt**

**European
Patent Office**

**Office européen
des brevets**

PM 17430

#2

Bescheinigung

Certificate

Attestation



Die angehefteten Unterla-
gen stimmen mit der
ursprünglich eingereichten
Fassung der auf dem näch-
sten Blatt bezeichneten
europäischen Patentanmel-
dung überein.

The attached documents
are exact copies of the
European patent application
described on the following
page, as originally filed.

Les documents fixés à
cette attestation sont
conformes à la version
initialement déposée de
la demande de brevet
européen spécifiée à la
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

99201296.3

Der Präsident des Europäischen Patentamts:
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets
p.o.

I.L.C. HATTEN-HECKMAN

DEN HAAG, DEN
THE HAGUE, 02/02/00
LA HAYE, LE

This Page Blank (uspto)



Europäisches
Patentamt

European
Patent Office

Office européen
des brevets

Blatt 2 der Bescheinigung
Sheet 2 of the certificate
Page 2 de l'attestation

Anmeldung Nr.:
Application no.: 99201296.3
Demande n°:

Anmeldetag:
Date of filing: 26/04/99
Date de dépôt:

Anmelder:
Applicant(s):
Demandeur(s):
Koninklijke Philips Electronics N.V.
5621 BA Eindhoven
NETHERLANDS

Bezeichnung der Erfindung:
Title of the invention:
Titre de l'invention:
System for providing personalized service

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:
State:
Pays:

Tag:
Date:
Date:

Aktenzeichen:
File no.
Numéro de dépôt:

Internationale Patentklassifikation:
International Patent classification:
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE
Etats contractants désignés lors du dépôt:

Bemerkungen:
Remarks:
Remarques:

This Page Blank (uspto)

System for providing personalized service.

FIELD OF THE INVENTION

The invention relates to a system for providing personalized service.

The invention further relates to an apparatus and a gatekeeper device for use in the above system.

- 5 The invention further relates to a method for providing a personalized service.

BACKGROUND OF THE INVENTION

A system of the above type is widely known. For example, it is known to store user profiles in consumer equipment to enable personalized operation in response to the user activating his
10 user profile, e.g. by means of an on-screen menu. Such a user profile may comprise information related to the user's favorite TV or radio channels and the presets they should be assigned to. It may further comprise information about preferred parameter settings such as sound level, picture contrast and brightness etc.

It is foreseen that in the near future an increasing number of apparatuses will store information
15 about personal data or preferences of users in order to adapt and/or personalize their behavior to a particular user. On the one hand this will lead to increased usability and efficiency. On the other hand user profiles have to be built up in the apparatuses involved and activated each time the apparatus is used. This may involve inserting a chip-card, or entering a password, which is inconvenient. Alternatively, the user may be recognized by automatic identification
20 (fingerprint, face or voice recognition, transponder technology), but a disadvantage of such systems is that privacy is not guaranteed.

OBJECT AND SUMMARY OF THE INVENTION

It is an object of the invention to provide an improved system of the type defined in the
25 opening paragraph. To that end, the system according to the invention comprises a gatekeeper device, capable of communicating an identity tag with at least one apparatus, the gatekeeper device comprising user operable control means for controlling said communication of identity tags, thus acting as a gatekeeper to prevent uncontrolled use of personal information by the apparatus to be operated. Said gatekeeper device may be a little tool which can be carried by

the user, e.g. in the form of a decoration. It enables the user to build anonymous relationships with various apparatuses. No personal identity codes and no biometric features need to be communicated, and the identity tags only have sense for one specific relationship. In response to the user expressing a wish to establish a relationship with an apparatus, e.g. by means of a suitable button on the gatekeeper device, an identity tag is generated to identify said relationship and stored in both the gatekeeper device and the apparatus. In a preferred embodiment, the apparatus and the gatekeeper device are capable of remote, e.g. RF, capacitive or infrared, communication.

Said control means enable the user to specify whether the gatekeeper device should be recognized by an apparatus to be operated, and to which extent the operated apparatus should adapt its behavior to the user. In the most simple embodiment, the user has the choice between personalized behavior and no personalized behavior. For example, the gatekeeper device may notify the user that an apparatus is approached which is capable of personalizing its behavior, and which already has a relationship with the gatekeeper device or which is capable of engaging in such a relationship. In a preferred embodiment the apparatus is not aware of the gatekeeper device until the user explicitly confirms that such a relationship may be established or exploited. In this way, the privacy and anonymity of the user is guaranteed.

In a further embodiment, the gatekeeper device allows the user to specify how the operated apparatus and the gatekeeper device have to communicate in subsequent occasions. For example, the user may specify, that the apparatus may automatically adapt its behavior as soon as the gatekeeper device is recognized, or under which conditions, e.g. only in the day time, and not in the evening or by night. The user may disable said automatic recognition at each of said subsequent occasions, e.g. by specifying that from that moment on an explicit confirmation by the user is required. Finally, the gatekeeper device may allow the user to terminate a relationship, causing the user profile to be removed and the identity tag be made invalid. A relationship may involve one specific apparatus exclusively, or it may involve multiple similar apparatuses, e.g. from the same manufacturer. A user profile may be stored with the identity tag in the gatekeeper device and transmitted each time to the apparatus to be operated. Alternatively, the user profile may be stored in the apparatus to be operated, waiting to be activated by the identity tag obtained from the gatekeeper device. In both cases the user profile may be shared with other apparatuses, e.g. by transmission through a network connecting the apparatuses, or by making the apparatuses respond to the same identity tag in order to obtain the user profile from the gatekeeper device. A relationship may involve

multiple user profiles which are selected by the user or automatically activated in accordance with certain conditions, e.g. the time of the day.

BRIEF DESCRIPTION OF THE DRAWINGS

5 These and other aspects of the invention are apparent from and will be elucidated, by way of a non-limitative example, with reference to the embodiment(s) described hereinafter. In the drawings,

Figure 1 shows a diagram of a system according to the invention, comprising various apparatuses and a gatekeeper device,

10 Figure 2 shows an embodiment of the gatekeeper device.

DESCRIPTION OF EMBODIMENTS

Figure 1 shows a diagram of a system according to the invention, comprising a gatekeeper device 1, and various apparatuses to be operated, such as an information terminal 2, a coffee machine 3 and an audio system 4. Each one of the apparatuses 2, 3 and 4 is capable of
15 adapting its behavior to a specific user in response to information obtained from the gatekeeper device 1. For example, the information terminal 2 tailors the information it provides to the knowledge and background of the user. The coffee machine 3 knows the user's taste and suggests this as a default choice. The audio systems compiles CD-tracks and adjusts
20 the sound parameters in accordance with the user's taste. The apparatuses 2, 3 and 4 continuously transmit a RF signal indicating that they are responsive to a gatekeeper device. Alternatively, infrared or ultrasound signals could be used or capacitive or inductive techniques may be utilized. If the gatekeeper device 1 approaches one of the devices 2, 3 or 4, it detects the RF signal and notifies the user, e.g. by a flashing light, a sound beep, or a
25 vibration. Dependent on the relationship which exists between the gatekeeper device 1 and the apparatus 2, 3 or 4, the gatekeeper device 1 may decide to send an identity tag to the apparatus autonomously, or leave that decision to the user. Upon receiving the identity tag, the apparatus can adapt its behavior to the user profile associated with the identity tag.

The gatekeeper device 1 is provided with user operable controls to allow the user to establish,
30 terminate or alter relationships with various apparatuses.

Figure 2 shows an embodiment of the gatekeeper device 1, referenced as the 'gatekeeper' henceforth. It comprises four buttons 5, 6, 7, and 8. The button 5 is used for switching the gatekeeper on and off. If the gatekeeper is switched off, the signals from all apparatuses are ignored, and no personalized behavior is exhibited. If the gatekeeper is switched on, various

situations may occur which will be discussed hereinafter. The buttons 6, 7 and 8 allow the user to make various choices with respect to the relationships with the apparatuses 2, 3, and 4. Button 6 has a red color and enables the user not to exploit the personalization capabilities of the apparatus (stay unrecognized). Button 7 has an orange color and enables the user to

5 establish an explicit relationship with the apparatus, which means that the user has to confirm each time the apparatus is used. Button 7 is combined with a LED which can make the button start to blink. Button 8 has a green color and enables the user to establish an implicit relationship with the apparatus, which means that the apparatus is allowed to adapt its behavior without confirmation by the user.

10 The following situations may occur:

1) New relationship:

If the gatekeeper is switched on and there is no relationship yet with the apparatus to be operated, the orange button 7 starts blinking, indicating that the apparatus is capable of engaging in such a relationship. If the user does nothing, no relationship is established and the

15 personalization capabilities of the apparatus are not exploited. The next time the apparatus is approached, the button 7 will start blinking again.

By pressing the red button 6, the user indicates that no relationship is desired, making the gatekeeper remember the apparatus and ignore the apparatus in the future, without notifying the user.

20 By pressing the orange button 7, the user indicates that he wishes to establish an explicit relationship. The apparatus associates an identity tag or key to the new relationship and transmits it to the gatekeeper, which stores the key for future identification to the apparatus. A user profile is then built up by watching the user's habits in operating the apparatus. Alternatively, a user profile related to a similar apparatus may be entered explicitly by the user

25 or transferred to the apparatus, either from a memory in the gatekeeper or via a network connecting the apparatus with similar apparatuses. The next time the apparatus is approached, the user is asked for a confirmation (by means of the blinking orange button 7). If the user confirms, the stored key is transmitted to the apparatus to identify the relationship and the user profile associated to the relationship is activated. If the user profile is stored in the gatekeeper,

30 it is transmitted to the apparatus.

By pressing the green button 8, the user indicates that he wishes to establish an implicit relationship. The same actions are performed as when pressing the orange button, thus establishing a new relationship, but the next time the apparatus is approached, the user is not

asked for confirmation, and the user profile associated to the relationship is activated automatically.

If the user pressed the red button a previous time, the gatekeeper does not notify the user if an apparatus is approached which is responsive to the gatekeeper. Nevertheless, the user can establish a relationship by pressing the orange or green button. Each successful action may be confirmed, e.g. by a beep or blinking LED.

2) Explicit relationship:

If the gatekeeper approaches an apparatus for which an explicit relationship exists, the gatekeeper recognizes the apparatus. This could be achieved in various ways. As described herein before, the apparatus initially identifies itself to the gatekeeper by transmitting a signal. This signal could comprise an 'apparatus key' which also constitutes a part of said identity tags or keys distributed by the apparatus to identify relationships with various gatekeeper devices. By comparing the apparatus key with the relationship keys stored in the gatekeeper, the apparatus can be recognized. Additionally, a 'manufacturer key' may be contained in the apparatus key, to identify the manufacturer of the apparatus. This enables the gatekeeper to recognize similar apparatuses from the same manufacturer and establishing relationships utilizing the same user profile. Alternatively, the gatekeeper explicitly relates the identity tags to the identity of the apparatus from which the tag was received.

Upon recognition of the apparatus, the orange button 7 starts blinking, waiting for the user's confirmation. If the user does nothing, the personalization capabilities of the apparatus are not exploited (this time). The user may confirm by pressing the button 7, thus activating the personalized behavior, or convert the explicit relationship into an implicit relationship by pressing the green button 8. The user may also terminate the explicit relationship by pressing the red button 6.

3) Implicit relationship:

If the gatekeeper approaches an apparatus with which an implicit relationship exists, the gatekeeper recognizes the apparatus as described hereinbefore. No confirmation by the user is awaited, and the personalized behavior is activated immediately. However, the user may decide to convert the implicit relationship into an explicit relationship by pressing the orange button 7, or by terminating the relationship at all by pressing the red button 6.

Although the invention has been described with reference to particular illustrative embodiments, variants and modifications are possible within the scope of the inventive concept.

Thus, for example, various user profiles may be involved in one relationship, each of which corresponding to personal information of a different level of confidentiality. For example, medical data relating to the user may be incorporated in a user profile, e.g. for searching a library catalogue, but not in every occasion, e.g. in the presence of bystanders.

- 5 The gatekeeper enables users to express different identities. People behave different at home, at work or in the pub. The gatekeeper is a tool that enables users to have control over their expressed identities. People may possess multiple gatekeepers, each having a different look and suited for a different situation. Wearing two or more gatekeepers in combination may have the effect that the user profiles are combined in some way.
- 10 Multiple gatekeepers may simultaneously control the behavior of one particular apparatus. For example, a message board or teleconference system which is shared by multiple users may allow each user to specify which personal information may be presented to the other users. For other parameters, such as sound level and picture brightness, the apparatus may attempt to find a compromise between the different values from the various user profiles.
- 15 The word 'comprising' does not exclude the presence of other elements or steps than those listed in a claim.

- In summary, the invention relates to a system for providing personalized service. The system comprises an apparatus which is capable of personalizing its behavior in accordance with a user profile, and a gatekeeper device comprising control means for allowing a user to control
- 20 said personalization of the apparatus. The gatekeeper device is capable of detecting apparatuses which have personalization capabilities and notifying the user upon such detect on. The user may then decide to establish a relationship with the apparatus, which relationship specifies the extent of personalization which the apparatus is allowed to exhibit and whether confirmation by the user is required at future occasions. The user is allowed to
- 25 change the relationship at any time. The system according to the invention enables the user to build anonymous relationships with various apparatuses, providing the user with personalized services while privacy is guaranteed.

CLAIMS

1. A system for providing a personalized service, comprising an apparatus which is capable of personalizing its behavior in accordance with a user profile, **characterized in that** the system further comprises a gatekeeper device for controlling said personalization, said gatekeeper device comprising user operable control means for adjusting the extent of said personalization.

2. A system as claimed in claim 1, **characterized in that** said control means comprise confirmation means for specifying that the apparatus is allowed to personalize its behavior.

3. A system as claimed in claim 1 or 2, **characterized in that** said control means comprise rejection means for specifying the apparatus is not allowed to personalize its behavior.

4. A system as claimed in any of claims 1 to 3, **characterized in that** the gatekeeper device is capable of detecting the nearness of the apparatus, the gatekeeper device further comprising notification means for notifying such a detection.

5. A system as claimed in claim 4, **characterized in that** the apparatus is capable of transmitting an identification signal for facilitating said detection.

6. A system as claimed in claim 1, **characterized in that** the gatekeeper device comprises further user operable control means for establishing a relationship with the apparatus, said relationship specifying the extent of personalization at subsequent occasions.

7. A system as claimed in claim 6, **characterized in that** the apparatus is capable of generating an identity tag which identifies said relationship and exchanging said identity tag with the gatekeeper device, the gatekeeper device being capable of storing said identity tag.

26-04-1999

EP99201296.3

SPEC

EP-P

8

26.04.1999

8. A system as claimed in any of claims 1 to 7, **characterized in that** the gatekeeper device is capable of storing at least one user profile, and exchanging said user profile with said apparatus.

5 9. A system as claimed in any of claims 1 to 8, **characterized in that** the apparatus is capable of exchanging a user profile with said gatekeeper device or a further apparatus.

10. A gatekeeper device for use in a system as claimed in any of claims 1 to 9.

10

11. An apparatus for use in a system as claimed in any of claims 1 to 19.

12. A method for providing a personalized service, utilizing a system as claimed in any of claims 1 to 9.

ABSTRACT

The invention relates to a system for providing personalized service. The system comprises an apparatus which is capable of personalizing its behavior in accordance with a user profile, and a gatekeeper device comprising control means for allowing a user to control said personalization of the apparatus. The gatekeeper device is capable of detecting
5 apparatuses which have personalization capabilities and notifying the user upon such detection. The user may then decide to establish a relationship with the apparatus, which relationship specifies the extent of personalization which the apparatus is allowed to exhibit and whether confirmation by the user is required at future occasions. The user is allowed to change the relationship at any time. The system according to the invention enables the user to
10 build anonymous relationships with various apparatuses, providing the user with personalized services while privacy is guaranteed.

Fig. 1

1/1




FIG. 1




FIG. 2